

QuickScan 6000 Plus™ Handheld Scanner

Checkout The Handheld Scanner That Is Setting The New Standard At Retail Checkout Around The World

- **Ideal for all in-store applications**
- **Fast and tough**
- **Affordable**

Great Performance is now even Better!

The QuickScan 6000 Plus™ handheld scanner offers great performance at a very affordable price. With a high first pass read rate and the best speed-to-read of any scanner in its class, the QS6000 Plus speeds retail checkout. And its 33 cm depth of field with 100% UPC labels extends the user's working range.

With a high visibility option, utilizing a 650nm laser diode, the user can target and read bar codes even in bright light conditions due to the scanner's inherent tolerance of high ambient light conditions. Plus, PSC's advanced electronics perform well even when reading low contrast labels with poor edge definition.

Hardened for Tough Store Environments

The QS6000 Plus scanner incorporates the most advanced, high durability features available today. The reading engine and optics are protected by anti-shock mounts built to absorb up to 1500 Gs. In fact, the QS6000 Plus can withstand repeated five-foot drops to concrete.

The QS6000 Plus also features a strong, plastic enclosure that guards against liquid and dust infiltration. A tough, rubber-like shield cushions the scanner when dropped, protects the scan window from scratching



and prevents the scanner from slipping off counter surfaces. The coiled cable, with strain relief and end cap, is made from rugged, tear-resistant polyurethane and retains its' memory after repeated flexing and stretching.

Lightweight & Ergonomic For Maximum Scanning Comfort & Productivity

The QS6000 Plus scanner was developed with operator comfort in mind — a critical factor that ensures prolonged operator productivity. The weight of its evenly balanced design can be held easily in any size hand, even during extended periods of use. The positive response trigger provides tactile feedback when pressed, yet allows the operator's index finger to relax comfortably between scans. When resting on a horizontal surface, in a stand, or in a belt holster, the handle is quickly and easily grasped for "scoop and scan" simplicity.

Connectivity For Any Environment

Support for all popular POS interfaces and keyboard wedges is standard. The QS6000 Plus reads all major bar code

sympologies, auto-discriminating between codes. Full support is also included for the UPC/EAN family, add-ons and other types of code extensions.

The QuickScan 6000 Plus: An Outstanding Value

With the QS6000 Plus scanner, there's no need to make trade-offs between quality and affordability. High-end performance, advanced ergonomic design, enhanced durability—the combination of these features in the QS6000 Plus adds up to one of the best values in the industry.

ADDITIONAL FEATURES

- *Low power consumption*
- *AutoSense™ stand for hands-free operation*
- *Dual interfaces with AutoSelect™*
- *Optional EAS antenna for simultaneous scanning and security tag deactivation*
- *Universal wedge for additional keyboard emulation, bar code symbologies and data editing*

PSC[®]

When You Need To Read A Bar Code

QuickScan 6000 Plus™ Handheld Scanner

SPECIFICATIONS

MECHANICAL

Dimensions	16,51 x 7,01 x 10,74 cm
Weight	
• Scanner	170 g
• Cable (81.3 cm)	176 g
Cable length options	<i>Collapsed:</i> 81 cm, <i>Max. Working:</i> 183 cm; <i>Collapsed:</i> 203 cm, <i>Max. Working:</i> 305 cm

(For other cable options, contact your PSC sales representative.)

OPTICAL

Light source	Visible Laser Diode (VLD) 680 nm-nominal (650 nm-optional)
Scan system	Electromagnetic dithering mirror
Rate	42 scans/sec. (nominal)
Depth of field	(printing resolution, contrast and ambient light dependent)
Label Density	Range
5 mil	2,5 - 7,6 cm
7.5 mil	1,3 - 15,2 cm
10 mil	0,0 - 22,9 cm
13 mil	0,0 - 33,0 cm
20 mil	up to 48,3 cm
Resolution	5 mils (0,13 mm)
Print contrast ratio	30% minimum
Pitch	±65°
Skew	±55°
Scan angle	46°
Ambient light immunity	<i>Artificial light:</i> 1,200 foot candles <i>Sunlight:</i> 8,000 foot candles

ELECTRICAL

Operating voltage	(NOTE: Specifications using the 680 nm laser diode & cable) 4.2V to 14VDC (undecoded); 3.8V to 20VDC (decoded)
Operating current - nominal	70mA at 5VDC (undecoded); 120mA at 5VDC (decoded)
Idling current - nominal	10µA at 5VDC (undecoded); 23mA at 5VDC (decoded); 14mA at 5VDC (decoded, lowest power mode)

DECODING CAPABILITY

- **UPC A, E / EAN 8, 13 / JAN 8, 13**
(P2 / P5, Code 128 EAN add-ons)
- **Code 128/EAN 128** • **Code 39**
- **Interleaved 2 of 5** • **Code 93**
- **Standard 2 of 5, IATA** • **Codabar**
- **Pharmacode 39** • **MSI / Plessey**

COMMUNICATIONS

(AutoSelect™ cable determines active interface)

- **IBM 4682 / 92** (Port E)
- **IBM 4683 / 84** (Ports 5B & 9B)
and Wand Emulation
- **IBM 4693 / 94** (Ports 5B & 9B)
and Wand Emulation
- **RS232 and IBM 46xx**
- **RS232 and Wand Emulation**
- **RS232 and Standard Keyboard Wedge**
- **OCIA** (SP & NCR formats) *and RS232*
- **Standard Keyboard Wedge and Wand Emulation**
- **Universal Keyboard Wedge**
- **Undecoded**

ENVIRONMENTAL

Temperature rating	
• Operating	0° to 50° C
• Storage	-40° to 70° C
Humidity	5 to 95% NC
Shock (at 23° C)	Withstands multiple five-foot drops onto concrete / 100+ drops to countertop.
Vibration	MIL-STD-810E
Water & Dust	Resistant, IEC529 rating IP53DW

SAFETY / REGULATORY

Electrical	Complies to: Gost R; TÜV; UL; cUL
Emissions	Complies to: FCC-A; EN 55022-B BCIQ CNS13438; AS/NZS 3548; VCCI-B
Laser classification	CDRH Class II; (CAUTION: Laser Radiation – do not stare into beam); IEC 60825 Class 1 & 2



Specifications apply to RS232 interface with 680nm VLD unless otherwise stated and are subject to change without notice.
For further information, contact your PSC representative.



Accessory mount also available.



PSC Worldwide Website: www.pscnet.com

When You Need To Read A Bar Code

Automation, Self-Checkout and Verification products:

PSC Inc., Corporate Headquarters
675 Basket Road
Webster NY 14580-9787 USA
For Information and Technical Support:
Tel: 1 716 265 1600 or 800 828 6489
Fax: 1 716 265 6400 • E-mail: mktg@pscnet.com



Attended Fixed and Handheld products:

PSC Inc.
959 Terry Street
Eugene OR 97402-9150 USA
For Information:
Tel: 1 541 683 5700 or 800 547 2507
Fax: 1 541 686 1702 • E-mail: mktg@pscnet.com



For Technical Support:
Tel: 1 541 683 5700 or 800 695-8700
Fax: 1 541 984 3092
E-mail: techsupport@pscnet.com

PDT, WMS and Decoder products:

PSC Inc.
1800 Millrace Drive
Eugene OR 97403-1992 USA
For Information:
Tel: 1 541 344 1189 or 800 929 7899
Fax: 1 541 344 1399 • E-mail: info@percon.com

PSC International Sales and Service locations:

European Headquarters
Europe/Middle East/Africa
PSC Bar Code Limited
Axis 3, Rhodes Way
Watford, England WD2 4YW
Tel: 44 0 1923 809500
Fax: 44 0 1923 809505

Belgium
Tel: 32 2 414-74.09
Fax: 32 2 410.11.63
Sweden
Tel: 46 0 40 10 84 90
Fax: 46 0 40 10 84 91

France
Tel: 33 0 1 64 86 71 00
Fax: 33 0 1 64 46 72 44
Turkey
Tel: 90 212 236 91 15
Fax: 90 212 236 91 16

Germany
Tel: 49 6151 9358-0
Fax: 49 6151 9358 58

Italy
Tel: 39 039 629031
Fax: 39 039 6859496

Spain
Tel: 34 9 1 656 7525
Fax: 34 9 1 656 8485

Asia Pacific Headquarters
PSC Hong Kong
12 Harcourt Road
Bank of America Tower 8th Floor
Hong Kong
Tel: 853 2 584 6210
Fax: 853 2 521 0291

Australian Headquarters
PSC Asia Pacific Pty Ltd
6-10 Talavera Road
Suite G 1
North Hyde NSW 2113
Tel: 61 0 2 9878 8999
Fax: 61 0 2 9878 8688

Japanese Headquarters
PSC Japan
Shuwa-Nishigotanda Bldg.
5-2-4 Nishigotanda
Shinagawa-Ku, Tokyo 141
Tel: 81 0 3 3491-6761
Fax: 81 0 3 3491-6656

Latin American Headquarters
PSC Latin America
1110 Brickell Avenue
Suite 505
Miami FL 33131 USA
Tel: 1 305 539-0111
Fax: 1 305 539-0206

Part No. R45-2014D 0600

PSC, PSC logo, and AutoSense are registered trademarks and QuickScan is a trademark of PSC Inc. All other brand and product names are trademarks of their respective owners.

Printed in U.S.A.
06/00 – 5M